

**LEAD
THE
FIELD.**

Land Roller



Level the Playing Field.

Prepare your field for superior combine performance with the all-new Brandt A-Series land roller. This efficient machine covers more ground in less time, levelling out your field while maximizing your seed-to-soil contact. And, its rugged design delivers superior uptime, ensuring that it's always ready to roll.

① Higher Output

The A-Series is purpose-built for uniform ground-contact and consistent results:

- Heavyweight 36" or 42"-diameter drum with up to 5/8" wall thickness delivers excellent rock rolling performance while extending the life of the drum.
- Hydraulic floating-hitch system and individual frame-section contouring maximize in-field flexibility.
- True drum overlap provides equal rolling pressure across the entire working width and ensures a consistent smooth field finish.

② Less Maintenance

This land roller utilizes a rugged design to deliver superior uptime that you can count on:

- Heavy-duty frame construction provides unmatched strength and fabrication quality.
- Durable 2.5" pivot pins with composite bushings improve machine durability and reduce maintenance.
- Premium 3" roller drum pin and sealed zero-maintenance bearings deliver years of worry-free operation.

③ Lower Operating Costs

This smart, built-to-last equipment helps you make the most of your investment:

- Steel hydraulic lines provide superior durability compared to common rubber hoses.
- Powder-coat paint and primer ensures long-lasting vibrant colouration, superior rust protection, and a higher resale value.
- Hydraulic hose management arm and premium hydraulic couplers extend the life of the tractor connections, reducing maintenance work.

Powerful Value. **Delivered.**

Brandt

LAND ROLLER SPECIFICATIONS

	351A	564A	582A
Performance			
Field Working Width	51'	64'	82'
Minimum Horsepower	150	200	250
Frame Sections	19.5' - 12.5' - 19.5'	12.5' - 12.5' - 15' - 12.5' - 12.5'	17' - 17' - 15' - 17' - 17'
Section Overlap	4"	4"	4"
Machine Weight (36"/42")	19,504 lbs / 21,375 lbs	28,659 lbs / 31,174 lbs	32,707 lbs / 35,744 lbs
Weight per ft. (36"/42")	382 lbs / 419 lbs	448 lbs / 487 lbs	399 lbs / 436 lbs
Drum Wall Thickness	≥0.46"	≥0.46"	≥0.46"
Frame			
Floating Hitch	Manual or Hydraulic Floating Hitch	Hydraulic Floating Hitch	Hydraulic Floating Hitch
Steel Mud Scrapers	Optional	Optional	Optional
Hitch Pole Thickness	4" x 6" x 1/4"	4" x 6" x 1/4"	4" x 6" x 1/4"
Center Frame Thickness	1/4"	3/8" & 1/4"	3/8" & 1/4"
Wing Frame Thickness	1/4"	3/8" & 1/4"	3/8" & 1/4"
Solid Pull Boom Thickness	1/4"	1/4"	1/4"
Center Frame Transport Cylinder (Bore x Stroke x Shaft)	4" x 16" x 2"	4" x 16" x 2"	4" x 16" x 2"
Floating Hitch Cylinder (Bore x Stroke x Shaft)	3-1/2" x 8" x 1-1/4"	3-1/2" x 8" x 1-1/4"	3-1/2" x 8" x 1-1/4"
Wing Boom Wheel Pivot Cylinder (Bore x Stroke x Shaft)	3" x 2" x 1-1/4"	3" x 2" x 1-1/4"	3" x 2" x 1-1/4"
U-Joint & Pivot Pin Diameter	2.5" w/ Maintenance Free Composite Bushings		
Drum Roller Bearing	Extreme Duty, No Maintenance Bearings		
Drum Roller Shaft Diameter	3"	3"	3"
Transport			
Wing Latching System	Hydraulic Draw-Arm Latching System		
Transport Transition	Hydraulic or Manual Fold	15° Pivoting Hydraulic End Wheel Assist	
Transport Hitch Weight	1,020 lbs	1,450 lbs	1,150 lbs
Width x Length x Height	13'10" x 49'2" x 7'	16'4" x 50'9" x 7'	16'4" x 59'9" x 7'
Tires			
Center Frame Tires (4)	12.5LX15FI	IF320/70R15	IF320/70R15
Wing Boom Tires (2)	12.5LX15FI	385/65R22.5	385/65R22.5
Hitch			
Standard Hitch	CAT 4	CAT 4	CAT 4
Optional Crossover Hitch	Yes	Yes	Yes
Optional Ball-Socket Hitch	CAT 4 or CAT 5	CAT 4 or CAT 5	CAT 4 or CAT 5

FEATURES

Optional Mud-scrappers

Prevents residue build-up and maintains optimal performance.

Hydraulic Wing-latching System

Enables fast and reliable transitions to and from the working position.

Steerable Transport Wheels

Makes unfolding the roller into the field position quick and simple.

Oversized Transport Tires

Dependably handles the roller transport weight.

CAT 4 & CAT 5 Hitch Options

Matches tractors' draw-pin size and enables up to 45° of pitch and roll.

For more information
Call us at 1-866-4-BRANDT
Email us at agriculture@brandt.ca
Or visit us at www.brandt.ca

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road
Regina, SK, Canada
S4P 3A1

