



Easy Jet by Air Bubble Jet

The same performance you've come to expect with the Air Bubble Jet, except designed specifically for PWM systems.



Features and Benefits:

- Made for PWM systems
- 2% driftable droplets compared to 25% or more with conventional tips
- 200-500 micron droplet size range with appx. 75% in the sweet spot range of 300-400
- Fits most holders or caps (same caps for Air Bubble Jet Tips as listed in the catalog)
- Life expectancy on average 70,000 acres

Easy Jet PWM Nozzle

Part	Description
AG430507	Size 015
AG430508	Size 025
AG430509	Size 03
AG430510	Size 04
AG430511	Size 05
AG430512	Size 06
AG430513	Size 08

Nozzle		Pressure	Flow	Speed MPH @ 20 Inch Nozzle Spacing																																							
		PSI	US Gal	25%					50%					75%					100%																								
				6					8					10					12					14					16					18					20				
				Quality					Quality					Quality					Quality					Quality					Quality					Quality									
Easy Jet Green 015	PSI	US Gal	Quality																																								
	30	0.13	M	1.6	3.2	4.8	6.4	1.2	2.4	3.6	4.8	1.0	1.9	2.9	3.9	0.8	1.6	2.4	3.2	0.7	1.4	2.1	2.8	0.6	1.2	1.8	2.4	0.5	1.1	1.6	2.1	0.5	1.0	1.4	1.9								
	40	0.15	M	1.9	3.7	5.6	7.4	1.4	2.8	4.2	5.6	1.1	2.2	3.3	4.5	0.9	1.9	2.8	3.7	0.8	1.6	2.4	3.2	0.7	1.4	2.1	2.8	0.6	1.2	1.9	2.5	0.6	1.1	1.7	2.2								
	60	0.18	M	2.3	4.5	6.8	9.1	1.7	3.4	5.1	6.8	1.4	2.7	4.1	5.5	1.1	2.3	3.4	4.5	1.0	1.9	2.9	3.9	0.9	1.7	2.6	3.4	0.8	1.5	2.3	3.0	0.7	1.4	2.0	2.7								
75	0.21	M	2.5	5.1	7.6	10.2	1.9	3.8	5.7	7.6	1.5	3.1	4.6	6.1	1.3	2.5	3.8	5.1	1.1	2.2	3.3	4.4	1.0	1.9	2.9	3.8	0.8	1.7	2.5	3.4	0.8	1.5	2.3	3.1									
Easy Jet Lilac 025	PSI	US Gal	Quality																																								
	30	0.22	C	2.7	5.4	8.0	10.7	2.0	4.0	6.0	8.0	1.6	3.2	4.8	6.4	1.3	2.7	4.0	5.4	1.1	2.3	3.4	4.6	1.0	2.0	3.0	4.0	0.9	1.8	2.7	3.6	0.8	1.6	2.4	3.2								
	40	0.25	M	3.1	6.2	9.3	12.4	2.3	4.6	7.0	9.3	1.9	3.7	5.6	7.4	1.5	3.1	4.6	6.2	1.3	2.7	4.0	5.3	1.2	2.3	3.5	4.6	1.0	2.1	3.1	4.1	0.9	1.9	2.8	3.7								
	60	0.31	M	3.8	7.6	11.4	15.2	2.8	5.7	8.5	11.4	2.3	4.5	6.8	9.1	1.9	3.8	5.7	7.6	1.6	3.2	4.9	6.5	1.4	2.8	4.3	5.7	1.3	2.5	3.8	5.1	1.1	2.3	3.4	4.5								
75	0.34	M	4.2	8.5	12.7	16.9	3.2	6.4	9.5	12.7	2.5	5.1	7.6	10.2	2.1	4.2	6.4	8.5	1.8	3.6	5.4	7.3	1.6	3.2	4.8	6.4	1.4	2.8	4.2	5.6	1.3	2.5	3.8	5.1									
Easy Jet Blue 03	PSI	US Gal	Quality																																								
	30	0.26	C	3.2	6.4	9.6	12.9	2.4	4.8	7.2	9.6	1.9	3.9	5.8	7.7	1.6	3.2	4.8	6.4	1.4	2.8	4.1	5.5	1.2	2.4	3.6	4.8	1.1	2.1	3.2	4.3	1.0	1.9	2.9	3.9								
	40	0.30	C	3.7	7.4	11.1	14.9	2.8	5.6	8.4	11.1	2.2	4.5	6.7	8.9	1.9	3.7	5.6	7.4	1.6	3.2	4.8	6.4	1.4	2.8	4.2	5.6	1.2	2.5	3.7	5.0	1.1	2.2	3.3	4.5								
	60	0.37	M	4.5	9.1	13.6	18.2	3.4	6.8	10.2	13.6	2.7	5.5	8.2	10.9	2.3	4.5	6.8	9.1	1.9	3.9	5.8	7.8	1.7	3.4	5.1	6.8	1.5	3.0	4.5	6.1	1.4	2.7	4.1	5.5								
75	0.41	M	5.1	10.2	15.3	20.3	3.8	7.6	11.4	15.3	3.1	6.1	9.2	12.2	2.5	5.1	7.6	10.2	2.2	4.4	6.5	8.7	1.9	3.8	5.7	7.6	1.7	3.4	5.1	6.8	1.5	3.1	4.6	6.1									
Easy Jet Red 04	PSI	US Gal	Quality																																								
	30	0.35	C	4.3	8.6	12.9	17.1	3.2	6.4	9.6	12.9	2.6	5.1	7.7	10.3	2.1	4.3	6.4	8.6	1.8	3.7	5.5	7.3	1.6	3.2	4.8	6.4	1.4	2.9	4.3	5.7	1.3	2.6	3.9	5.1								
	40	0.40	C	5.0	9.9	14.9	19.8	3.7	7.4	11.1	14.9	3.0	5.9	8.9	11.9	2.5	5.0	7.4	9.9	2.1	4.2	6.4	8.5	1.9	3.7	5.6	7.4	1.7	3.3	5.0	6.6	1.5	3.0	4.5	5.9								
	60	0.49	C	6.1	12.1	18.2	24.2	4.5	9.1	13.6	18.2	3.6	7.3	10.9	14.5	3.0	6.1	9.1	12.1	2.6	5.2	7.8	10.4	2.3	4.5	6.8	9.1	2.0	4.0	6.1	8.1	1.8	3.6	5.5	7.3								
75	0.55	M	6.8	13.6	20.3	27.1	5.1	10.2	15.3	20.3	4.1	8.1	12.2	16.3	3.4	6.8	10.2	13.6	2.9	5.8	8.7	11.6	2.5	5.1	7.6	10.2	2.3	4.5	6.8	9.0	2.0	4.1	6.1	8.1									
Easy Jet Brown 05	PSI	US Gal	Quality																																								
	30	0.43	C	5.4	10.7	16.1	21.4	4.0	8.0	12.1	16.1	3.2	6.4	9.6	12.9	2.7	5.4	8.0	10.7	2.3	4.6	6.9	9.2	2.0	4.0	6.0	8.0	1.8	3.6	5.4	7.1	1.6	3.2	4.8	6.4								
	40	0.50	C	6.2	12.4	18.6	24.8	4.6	9.3	13.9	18.6	3.7	7.4	11.1	14.9	3.1	6.2	9.3	12.4	2.7	5.3	8.0	10.6	2.3	4.6	7.0	9.3	2.1	4.1	6.2	8.3	1.9	3.7	5.6	7.4								
	60	0.61	C	7.6	15.2	22.7	30.3	5.7	11.4	17.1	22.7	4.5	9.1	13.6	18.2	3.8	7.6	11.4	15.2	3.2	6.5	9.7	13.0	2.8	5.7	8.5	11.4	2.5	5.1	7.6	10.1	2.3	4.5	6.8	9.1								
75	0.68	C	8.5	16.9	25.4	33.9	6.4	12.7	19.1	25.4	5.1	10.2	15.3	20.3	4.2	8.5	12.7	16.9	3.6	7.3	10.9	14.5	3.2	6.4	9.5	12.7	2.8	5.6	8.5	11.3	2.5	5.1	7.6	10.2									
Easy Jet Grey 06	PSI	US Gal	Quality																																								
	30	0.52	VC	6.4	12.9	19.3	25.7	4.8	9.6	14.5	19.3	3.9	7.7	11.6	15.4	3.2	6.4	9.6	12.9	2.8	5.5	8.3	11.0	2.4	4.8	7.2	9.6	2.1	4.3	6.4	8.6	1.9	3.9	5.8	7.7								
	40	0.60	VC	7.4	14.9	22.3	29.7	5.6	11.1	16.7	22.3	4.5	8.9	13.4	17.8	3.7	7.4	11.1	14.9	3.2	6.4	9.5	12.7	2.8	5.6	8.4	11.1	2.5	5.0	7.4	9.9	2.2	4.5	6.7	8.9								
	60	0.73	VC	9.1	18.2	27.3	36.4	6.8	13.6	20.5	27.3	5.5	10.9	16.4	21.8	4.5	9.1	13.6	18.2	3.9	7.8	11.7	15.6	3.4	6.8	10.2	13.6	3.0	6.1	9.1	12.1	2.7	5.5	8.2	10.9								
75	0.82	VC	10.2	20.3	30.5	40.7	7.6	15.3	22.9	30.5	6.1	12.2	18.3	24.4	5.1	10.2	15.3	20.3	4.4	8.7	13.1	17.4	3.8	7.6	11.4	15.3	3.4	6.8	10.2	13.6	3.1	6.1	9.2	12.2									
Easy Jet White 08	PSI	US Gal	Quality																																								
	30	0.69	XC	8.6	17.1	25.7	34.3	6.4	12.9	19.3	25.7	5.1	10.3	15.4	20.6	4.3	8.6	12.9	17.1	3.7	7.3	11.0	14.7	3.2	6.4	9.6	12.9	2.9	5.7	8.6	11.4	2.6	5.1	7.7	10.3								
	40	0.80	XC	9.9	19.8	29.7	39.6	7.4	14.9	22.3	29.7	5.9	11.9	17.8	23.8	5.0	9.9	14.9	19.8	4.2	8.5	12.7	17.0	3.7	7.4	11.1	14.9	3.3	6.6	9.9	13.2	3.0	5.9	8.9	11.9								
	60	0.98	VC	12.1	24.2	36.4	48.5	9.1	18.2	27.3	36.4	7.3	14.5	21.8	29.1	6.1	12.1	18.2	24.2	5.2	10.4	15.6	20.8	4.5	9.1	13.6	18.2	4.0	8.1	12.1	16.2	3.6	7.3	10.9	14.5								
75	1.10	VC	13.6	27.1	40.7	54.2	10.2	20.3	30.5	40.7	8.1	16.3	24.4	32.5	6.8	13.6	20.3	27.1	5.8	11.6	17.4	23.2	5.1	10.2	15.3	20.3	4.5	9.0	13.6	18.1	4.1	8.1	12.2	16.3									