LEAD THE FIELD.



XT GrainCarts

Overdeliver.

The all-new XT GrainCart from Brandt delivers industry-leading auger reach for easy positioning and clear visibility that allows you to move more grain, faster.

① Productivity

These carts are designed for quick turnaround and smooth, intuitive in-field operation:

- Industry-leading auger reach delivers the ultimate in operator unload visibility.
- Low-profile tank and tarp design reduces height and delivers maximum combine auger clearance.
- Steep tank angles deliver quick, complete tank cleanout every unload cycle.

② Unrivalled Uptime

XT Series GrainCarts are built with reliable components for long-term dependability:

- Dependable straight-auger design delivers superior reliability and performance.
- Anti-shock auger coupler extends gearbox and driveline lifespan.
- Cushioned auger-fold cylinders are purpose-built for extended auger-fold cycling.

③ Low Operating Cost

Leading performance, reliability, and resale value make the XT GrainCart a solid investment:

- The modular frame and tank design allows for strong, easily-replaceable components.
- Brandt's rugged powder coat paint process optimizes tank cleanout, rust protection, component life, and resale value.
- Half-inch-thick extended-life flighting provides unmatched auger durability.

XT GRAINCARTS
SPECIFICATIONS

	1520XT	1320XT	1120XT	1020XT	820XT
Performance					
Capacity (bushels)	1500	1300	1100	1000	850
Unload Speed (bu/min)	600	600	600	600	600
Minimum Horsepower	300	250	200	200	200
General					
Auger Diameter	20"	20"	20"	20"	20"
Flighting	1/2" Extended Life	1/2" Extended Life	1/2" Extended Life	1/2" Extended Life	1/2" Extended Life
Dimensions					
Auger Forward Reach (ahead of hitch)	8'3"	8'3"	8'3"	8'3"	8'3"
Auger Upward Reach (bottom of spout)	13'2"	13'2"	13'2"	13'2"	13'2"
Auger Side Reach (hitch to spout)	15'8"	15'8"	15'8"	15'8"	15'8"
Loading Side Height	11'8"	11'1"	11'3.5"	10'10"	11'
Transport Height	13'1"	12'6"	12'10.5"	12'5"	12'
Overall Height (with auger extended)	18'3"	18'3"	18'3"	18'3"	18'3"
Overall Length	32'4"	32'4"	31'9"	31'9"	31'9"
Width (varies by undercarriage)	13'–15'6"	13'–15'6"	12'10"–16'3.5"	12'10"–16'3.5"	12'10"–16'3.5"
Undercarriage					
Options	Tracks/Tires	Tracks/Tires	Rigid Axle Tires Adjustable Axle Tracks/Tires	Rigid Axle Tires Adjustable Axle Tracks/Tires	Rigid Axle Tires Adjustable Axle Tracks/Tires

FEATURES

Twenty-inch double-pitch auger

double-pitched lower flighting allows an unload capacity of up to 600 bu/min.

Standard four-direction spout

lets you direct grain flow without moving the cart.

Tough driveline & gearbox

ensures that the gearbox input shaft receives steady power, free of any wobble.

Exclusive ground-level access hatch

allows operators to easily enter the grain cart tank from the ground-level while eliminating any chance of leakage.

Robust five-point load bar system

delivers the most accurate and durable load-cell structure on the market.

Brandt Advanced Paint Protection

looks better, lasts longer, and is now available in blue, green, or red to match your other equipment.

Options to fit your needs

including joystick control kit, auto-locking auger fold valve, LED flowgate position indicator, fire suppression kit, hydraulic jack stand, and front-mount tank viewing ladder.



Now available in red.

For more information
Call us at 1-866-4-BRANDT
Email us at **agriculture@brandt.ca**
Or visit us at **www.brandt.ca**

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road,
Regina, SK, Canada
S4P 3A1

LEAD THE FIELD.



DXR GrainCarts

Speed Up Your Harvest.

Brandt's dual-auger DXR-Series grain carts deliver full capacity with any product, under any conditions to meet the rigorous demands of a fast-paced harvest. They are available in 1150, 1500, and 2000-bushel sizes to suit your operational needs with minimal downtime.

① Quick Turnaround

DXR grain carts deliver grain to your trucks quickly:

- The belt-driven 20" floor auger and heavy-duty 22" vertical auger enable unload speeds of up to 800 bu/min.
- The vertical auger has an industry-leading range of motion in height adjustment with over 7 ft. of travel ensuring fast, worry-free positioning.
- The discharge spout automatically rotates to a safe transport position so you can spend less time at the truck and back to your combine quicker.

② Total Cleanout

Longer, narrower tank design delivers fast complete tank cleanout on every cycle:

- Steep, ledge-free tanks with round cross-supports ensure there are no hang-up points to prevent grain flow.
- Full-length cleanout doors make crop switching or end-of-season maintenance simple and fast.
- Loading-side heights as low as 11' guarantee safe and easy combine unloading on any terrain.

③ Accurate Load Management

Load your truck at the correct weight while keeping accurate track of grain inventory:

- A five-point scale system ensures your trucks are loaded to the exact weight you need.
- Digi-Star Scale data management system allows you to keep track of your harvest; including GPS, moisture levels, and wifi modules for comprehensive data tracking.
- Autolog technology automatically captures detailed data the minute you engage the tractor's PTO. And, Auto Unload automatically stops when you hit a pre-set load to ensure you don't overfill the truck.

DXR GRAINCARTS
SPECIFICATIONS

	1122DXR			1522DXR		2022DXR	
Performance							
Capacity (bushels)	1,150			1,500		2,000	
Unload Speed (bu/min)	800			800		800	
Minimum Horsepower	225+			300+		400+	
Auger Diameter	20" Horizontal into 22" Vertical			20" Horizontal into 22" Vertical		20" Horizontal into 22" Vertical	
Flighting	1/2" Extended Life			1/2" Extended Life		1/2" Extended Life	
Adjustable Discharge Travel	91°			91°		91°	
Undercarriage	**High Flotation**	**Extreme Flotation**	**Tracks**	**Tandem**	**Tracks**	**Tandem**	**Tracks**
Tire/Track Size	LSW1100/45R46	IF1250/50R32	136" x 36"	900/60R32	147" x 36"	IF900/60R32 CFO	170" x 36"
Tire Load Index	195	201	n/a	185	n/a	188-A8	n/a
Axle Spindle Diameter	5.5"	5.5"	5.5"	3.75"	5.5"	4.5"	5.5"
Loaded Surface Ground Pressure (psi)	37	33	13	47	14	41	15
Weight							
Empty (lb)	19,500	20,000	29,500	29,000	31,500	30,780	33,700
Tongue - Empty (lb)	3,600	3,600	3,600	3,900	3,900	4,340	4,340
Tongue - Full (lb)	5,200	5,200	5,200	5,700	5,700	5,175	5,175
Dimensions							
Height Hitch	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"	1'4" - 1'9"
Axle to Tongue Length	18' 3"	18' 3"	18' 3"	21'	21'	22' 4"	22' 4"
Overall Length	27' 7"	27' 7"	27' 7"	33'	33'	36'	36'
Hopper Length	18' 4"	18' 4"	18' 4"	24'	24'	27' 5"	27' 5"
Discharge Height	9'10" - 16'11"	9'10" - 16'11"	9'10" - 16'11"	9'5" - 16'6"	9'5" - 16'6"	9'9" - 16'10"	9'9" - 16'10"
Auger Reach	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"	5'3" - 9'3"
Overall Width	13' 2"	13' 2"	13' 2"	12' 9"	12' 9"	13' 11"	13' 11"
Minimum Hopper Height	11' 5"	11' 2"	11'	11'	11'	11' 6"	11' 6"
Loading Side Height	11' 5"	11' 2"	11'	11'	11'	11' 6"	11' 6"
Transport Height	12' 11"	12' 8"	12' 6"	12' 6"	12' 6"	12' 6"	12' 6"
Ground Clearance	1' 6"	1' 2"	1' 2"	10"	1' 2"	1' 2"	1' 2"
Wheel Inside Width	5' 11"	5' 5"	6' 2"	7' 6"	6' 2"	7' 5"	6' 10"
Wheel Track Width	9' 6"	9' 6"	9' 2"	10' 5"	9' 2"	10' 6"	9' 10"
Wheel Outside Width	13' 2"	13' 8"	12' 2"	13' 3"	12' 2"	13' 7"	12' 10"

OPTIONS

Hydraulic brakes

Camera kit

Enhanced lighting kit

Electric tarp

Joystick control kit

Undercarriage:

- Extreme flotation tires
- Steerable tandem axles
- Brandt's purpose-built track system

For more information
Call us at 1-866-4-BRANDT
Email us at **agriculture@brandt.ca**
Or visit us at **www.brandt.ca**

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road,
Regina, SK, Canada
S4P 3A1

Brandt