LEAD THE FIELD.



10HP

Swing Away Augers

Full Speed Ahead.

The 10HP Swing Away Auger from Brandt reduces truck unload times to get you back to the field even faster during busy harvest seasons. And, these augers are available in 60', 70', and 80' lengths to deliver ultimate versatility. The 10HP model is the ideal combination of high capacity, reliability, and ease of use that you need to get the job done.

① Faster Speeds

Brandt swing away augers are faster than ever to ensure you get more done in less time:

- The innovative HP technology feeds the 10" main flighting with the 11" swing flighting to achieve a capacity of up to 7,200 bu/hr.
- The low-clearance 70" x 40" hopper makes positioning under trailer hoppers easier than ever. And, it features flat-free tires for trouble-free use during harvest.
- The EZSWING hopper mover is available with electronic controls to guarantee easy maneuvering with a remote control or the LeadHand mobile app.

② Longer Lasting

Depend on your auger to serve you well for many seasons:

- Brandt's extended-life auger flighting is thicker at the edges where the most wear typically occurs to keep your auger running longer and more efficiently.
- The heavy-duty scissor lift delivers maximum reach, clearance, and low transport height while the standard monotube undercarriage improves safety, stability, and product life.
- Quick and easy access to the gearbox, u-joints, and the ability to reverse the auger allows for a complete cleanout.

③ Easier Maintenance

Protect your investment and increase resale value with Brandt's innovative design:

- Two robust easy-access clean-out doors on the transition ensure easy maintenance. And, the transition spout is sealed completely to keep your product in and moisture out.
- Designed with a chain coupler between the swing tube flighting and the gearbox for worry-free maintenance. The coupler absorbs shocks and protects the gearbox, increasing its longevity.
- Brandt's superior powder-coat paint optimizes cleanout, rust protection, and component life to increase your resale value.

10HP SWING AWAY AUGERS
SPECIFICATIONS

	1060HP	1070HP	1080HP
Performance			
Capacity (bushels per hour)	7,200	7,200	7,200
Recommended Horsepower	95	105	115
Dimensions			
Tube Diameter	10"	10"	10"
Length	60'	70'	80'
Height – Lowered / Raised	9' 8" / 42'	11' / 48' 6"	11' 6" / 52' 9"
Reach – Lowered / Raised	25' 6" / 16' 6"	35' 6" / 22' 6"	42' 8" / 30'
Transport Length	62' 3"	72' 2"	82' 2"
Transport Height	12' 4"	12' 6"	13' 6"
Wheel Track Width	11' 10"	11' 10"	11' 10"
Tube Thickness	13 ga	13 ga	13 ga
Flighting – Main / Swing Away	3/16" / 3/8"	3/16" / 3/8"	3/16" / 3/8"
Core Diameter	2"	2"	2"
Lower Bearing Size	1-3/8"	1-3/8"	1-3/8"
Gearbox Shaft Diameter	1-1/4"	1-1/4"	1-1/4"
Hitch Weight (lb)	500	850	850
Total Weight (lb)	3,460	3,600	4,380
Undercarriage			
Lift Mechanism	Scissor	Scissor	Scissor
Frame Arms	6" x 8" x 3/16"	6" x 8" x 3/16"	6" x 8" x 1/4"
Axle	4" x 4" x 3/16"	4" x 4" x 3/16"	4" x 4" x 3/16"
Hydraulic Cylinder Size	3.5" x 30"	4"x 30"	4.5" x 30"
Number of Hydraulic Cylinders	1	1	1
Hydraulic Requirements (psi)	1,600	1,400	1,400
Tire Size	ST205/75R15	ST205/75R15	ST235/75R15
Tire Ply Rating	6 Ply	6 Ply	8 Ply
Self-Leveling Swing Away Hopper			
Length x Width x Height	70" x 40" x 10"	70" x 40" x 10"	70" x 40" x 10"
Height w/ Extension	17"	17"	17"
# of Horizontal Flights	2	2	2
# of Wheels	4	4	4
Wheel Size	10"	10"	10"

OPTIONS

Man/hyd/elec winch

Man/hyd/elec EZSWING hopper mover

Right-angle drive

Reversing kit

Plastic bucket spout

No-snag bucket spout

Hopper cover

Safety light kit

Work light kit

For more information
Call us at 1-866-4-BRANDT
Email us at **agriculture@brandt.ca**
Or visit us at **www.brandt.ca**

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road,
Regina, SK, Canada
S4P 3A1

Brandt

LEAD THE FIELD.



13XL+ & 13HP+

Swing Away Augers

Move Faster. Reach Further.

Spend less time at the bin and more time in the field with Brandt's 13" Swing Away Augers. The XL+ and HP+ augers provide the optimal fit and versatility needed for any farm and are available in 70', 80', 90', and 110' lengths. 13XL+ models deliver an impressive 11,000 bu/hr, while the HP+ models deliver an industry-leading 13,000 bu/hr.

① Better Performing

Brandt swing away augers are faster than ever to ensure you get more done in less time:

- HP+ models optimize the flow of grain from the hopper through the 14" swing tube and into the 13" main auger resulting in industry-leading capacities with less flow-resistance.
- Move your crop, not your trailer with the all-new, fastest-ever EZReach extendable swing hopper for 13HP+ augers, featuring a 25% larger hopper to speed up your operation.
- Brandt's extended-life auger flighting is thicker at the edges where the most wear typically occurs to keep your auger running longer and more efficiently.

② Easier To Use

The user-friendly design ensures you stay productive during a fast-paced harvest:

- The EZSWING hopper mover is available with electric controls to guarantee easy maneuvering with a remote control or the LeadHand mobile app.
- The heavy-duty scissor lift delivers maximum reach, clearance, and low transport height while a standard monotube undercarriage improves safety, stability, and product life.
- The 70" x 40" hopper makes positioning under trailer hoppers easier than ever. And, it features flat-free tires for trouble-free use during harvest.

③ Longer Lasting

Protect your investment with Brandt's innovative design:

- Two robust easy access clean-out doors on the transition ensure easy maintenance. And, the transition spout is sealed completely to keep your product in and moisture out.
- Designed with a chain coupler between the swing tube flighting and the gearbox for worry-free maintenance. The coupler absorbs shocks and protects the gearbox, increasing its longevity.
- Brandt's superior powder-coat paint optimizes cleanout, rust protection, and component life to increase your resale value.

13XL+ & 13HP+ SWING AWAY AUGERS

SPECIFICATIONS

	1370XL+	1380XL+	1390XL+	13110XL+	1370HP+	1380HP+	1390HP+	13110HP+
Performance								
Capacity (bushels per hour)	11,000	11,000	11,000	11,000	13,000	13,000	13,000	13,000
Recommended Horsepower	150	160	170	180	175	195	215	235
Tractor PTO RPM	540	540	540	540	1,000	1,000	1,000	1,000
Dimensions								
Diameter – Tube / Swing Away	13" / 13"	13" / 13"	13" / 13"	13" / 13"	13" / 14"	13" / 14"	13" / 14"	13" / 14"
Length	70'	80'	90'	110'	70'	80'	90'	110'
Height – Lowered / Raised	9' 6" / 48' 7"	10' 9" / 55' 3"	11' 11" / 61' 11"	12' 10" / 73'	9' 6" / 48' 7"	10' 9" / 55' 3"	11' 11" / 61' 11"	12' 10" / 73'
Reach – Lowered / Raised	33' 3" / 22' 9"	43' 1" / 29' 6"	53' / 36' 11"	61' 9" / 46' 2"	33' 3" / 22' 9"	43' 1" / 29' 6"	53' / 36' 11"	61' 9" / 46' 2"
Transport Length	72' 9"	82' 8"	92' 9"	112' 6"	72' 9"	82' 8"	92' 9"	112' 6"
Transport Height	13' 2"	13' 2"	13' 8"	15' 3"	13' 2"	13' 2"	13' 8"	15' 3"
Wheel Track Width	12' 4" - 14' 10"	12' 4" - 14' 10"	12' 4" - 14' 10"	13' 4" - 16' 4"	12' 4" - 14' 10"	12' 4" - 14' 10"	12' 4" - 14' 10"	13' 4" - 16' 4"
Tube Thickness	12 ga	12 ga	12 ga	12 ga	12 ga	12 ga	12 ga	12 ga
Flighting – Main / Swing Away	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"
Core Diameter	3"	3"	3"	3"	3"	3"	3"	3"
Lower Bearing Size	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"
Gearbox Shaft Diameter	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"
Weight – Hitch / Total (lb)	1,500 / 6,300	1,270 / 6,900	1,050 / 7,100	1,510 / 9,300	1,700 / 6,500	1,470 / 7,100	1,210 / 7,300	1,740 / 9,500
Undercarriage								
Lift Mechanism	Scissor	Scissor	Scissor	Scissor	Scissor	Scissor	Scissor	Scissor
Frame Arms	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated
Axle	4"x4"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4"x6"x3/16"
Hydraulic Cylinder Size	4" x 36"	5" x 36"	5" x 36"	5" x 36"	4" x 36"	5" x 36"	5" x 36"	5" x 36"
Number of Hydraulic Cylinders	2	2	2	2	2	2	2	2
Hydraulic Requirements (psi)	1,050	1,100	1,600	1,950	1,050	1,100	1,600	1,950
Tire Size	ST225/75R15	ST235/85R16	ST235/85R16	ST235/85R16	ST225/75R15	ST235/85R16	ST235/85R16	ST235/85R16
Tire Ply Rating	8 Ply	8 Ply	8 Ply	12 Ply	8 Ply	8 Ply	8 Ply	12 Ply
Self-Leveling Swing Away Hopper								
Length x Width x Height	70"x 40"x10"	70"x40"x10"	70"x40"x10"	70"x40"x10"	70"x 40"x10"	70"x40"x10"	70"x40"x10"	70"x40"x10"
Height w/ Extension	17"	17"	17"	17"	17"	17"	17"	17"
# of Horizontal Flights	2	2	2	2	2	2	2	2
# of Wheels	4	4	4	4	4	4	4	4
Wheel Size	10"	10"	10"	10"	10"	10"	10"	10"

OPTIONS

Man/hyd/elec winch

Man/hyd/elec EZSWING hopper mover

AugerSteer hydraulic steering kit

Right angle drive

Reversing kit (13XL+)

Safety light kit

Hopper Cover

Work light kit

For more information
Call us at 1-866-4-BRANDT
Email us at **agriculture@brandt.ca**
Or visit us at **www.brandt.ca**

Brandt Agricultural Products
PO Box 317, 13th Avenue & Pinkie Road,
Regina, SK, Canada
S4P 3A1

Brandt